

Can be used for literally hundreds of applications on anything or anywhere a flexible textured coating is required, indoors or outdoors. For vehicle traffic we strongly recommend using black to hide tire marks.

APPLICATION:

ArmorTrak is sold as a per square foot product to ensure you have enough material to complete your project properly.

For all surfaces other than concrete, wood and previously coated surfaces, Bonding Primer must be used first. Wood and previously coated surfaces should be rough sanded clean, concrete surfaces, ceramic and porcelain tiles should be acid etched with muriatic acid in a 3 parts water to 1 part acid ratio and then neutralized with TSP at 1lb/1000 sf. In general all surfaces must be clean and dry prior to application of the ArmorTrak Coating.

Once surface is clean and dry, application is simple. If using the Bonding Primer, stir contents in can till uniform in color. Apply with lint free 3/8" nap roller and let dry overnight. Coverage of primer is 400 sf/gal.

Mix ArmorTrak in can with jiffy mixer in electric drill on medium speed to suspend rubber granules, do not shake can to stir. Apply ArmorTrak first coat with supplied ArmorTrak roller. First coat should go on thin to cover surface. Allow first coat to dry to the touch usually 3-4 hrs. Apply the second coat perpendicular to first coat if possible with the textured ArmorTrak roller. Second coat will get better coverage and should even out the look. ArmorTrak can be applied by brush where coating with roller is not feasible.

Allow to dry overnight prior to foot traffic. ArmorTrak should be allowed to dry for 24hrs before light traffic. Once ArmorTrak has fully cured in 48 hrs it is as tough as nails and will provide many years of service.

PLEASE NOTE THAT THE MINIMUM ORDER SIZE 150 SF AND THEN IN 75 SF INCREMENTS. ORDERS FOR LESS THAN 150 SF WILL NOT BE PROCESSED.